



# The Islamia University of Bahawalpur

## TENDER NOTICE

Sealed Tenders on item wise rate basis are invited from the Manufacturing Firms or their Authorized Distributors, Dealers and General order Suppliers having established credentials in terms of Technical, Financial and Managerial capabilities for the supply of **Instrument & Equipment, Department of Parasitology**, The Islamia University of Bahawalpur on FOR basis.

Tender No.	Category (Quantity and specifications are available in the tender document)	Estimated Cost	5% Bid Security
A	<b>Purchase of Instrument / Equipment Department of Parasitology</b>	<b>Rs.1,887,000/-</b>	<b>Rs.94,350/-</b>

- Interested bidders may get the Tender Documents containing detailed specifications, terms and conditions from the Purchase Section, Account Department Abbasia Campus (Old), the Islamia University of Bahawalpur during office hours on submission of written application on letter head and a copy of CNIC or can be down loaded from the IUB website [www.iub.edu.pk](http://www.iub.edu.pk) OR PPRA website [www.ppra.punjab.gov.pk](http://www.ppra.punjab.gov.pk) on payment of (non-refundable fee) of RS.1000/ (Separately for each category) through Bank challan HBL in A/C 14730000010403 or pay order in the name of the Treasurer, The Islamia University of Bahawalpur . Original receipt should be attached with Technical bid.
- 5% Bank Guarantee** of the estimated cost as mentioned above separately against each tender (Refundable) in the shape of CDR / Bank Guarantee. **The Original CDR shall be attached with the technical bid & copy of CDR should be attached with financial bid.**
- The rates should be quoted on FOR basis.
- Single Stage – Two Envelopes** bidding procedure will be adopted as per PPRA Rules 38- 2(a). The Envelopes shall be marked as “**TECHNICAL PROPOSAL**” AND “**FINANCIAL PROPOSAL**” in legible letters. Financial Proposal of bids found technically non-responsive shall be returned un-opened.
- Procurement shall be governed under the Punjab Procurement Rules, 2014.
- The rates should be quoted inclusive of all taxes. Copy of paid bank challan of professional tax and copy of the bid security shall be attached with the technical proposal.
- The Islamia University of Bahawalpur however, reserves the rights to reject all bids at any time prior to acceptance of a bid as per clause 35 of the Punjab Procurement Rules and grounds of rejection will be conveyed to the bidders upon their request.
- Tender should reach in the Office of the Secretary SMPC Accounts Division Old Campus, The Islamia University of Bahawalpur up to **02.03.2023** by **10:30 A.M.** Tenders will be opened on the same day at **11:00 A.M.** in the presence of bidders or their representatives. In the office of Chairman Purchase Committee, Pharmacy department Khawaja Fareed Campus.
- Any bid submitted after the given time schedule shall not be accepted.
- All taxes will be applicable as per Govt. Rules & Regulations.
- The rates should be valid upto 120-days from the date of opening of the tender.
- In case of closed/forced holidays, tender opening time/date will be considered as the next working day.



Chairman SMPC  
The Islamia University of Bahawalpur  
Baghdad-ul-Jadeed Campus, Bahawalpur.  
Phone: 062-9255565



# The Islamia University of Bahawalpur

## PROCUREMENT OF INSTRUMENT / EQUIPMENT FOR DEPARTMENT OF PARASITOLOGY TENDER-A FORM (FINANCIAL BID) Project based

1. Name of Firm: \_\_\_\_\_
2. Mailing Address: \_\_\_\_\_
3. Phone No: \_\_\_\_\_ 4. Fax No: \_\_\_\_\_
5. Tender Fee Challah No. & amount \_\_\_\_\_ 6.CDR No.& Amount \_\_\_\_\_
7. General Sale Tax No: \_\_\_\_\_ 8. Income Tax No. \_\_\_\_\_
9. Professional Tax No: \_\_\_\_\_

Sr	Name of Items	Quantity	Rate per item inclusive
01	<p>Ultra Low Temperature Freezer (-86 °C)  <b>Capacity:</b> 410L  <b>Temperature Range:</b> -40°C ~ 86°C  <b>Ambient Temperature:</b> 16°C – 32°C  <b>Cooling Performance:</b> -86°C  <b>Climate Class:</b> N  <b>Controller:</b> Microprocessor  <b>Display:</b> Touch Screen  <b>Compressor:</b> 2pcs (if one is damaged the other one give backup)  <b>Cooling Method:</b> Direct Cooling  <b>Refrigerant:</b> Mixture Gas  <b>Data Logging / Interval/ Recording Time:</b> USB/Record every 1 minute / 365 days  <b>Access Port:</b> 2pc. Ø 25 mm  <b>Door Lock with Key:</b> Yes  <b>External Lock:</b> Yes  <b>External Material:</b> High quality steel plates with spraying  <b>Internal Material:</b> Galvanized steel sheet  <b>Shelves:</b> 3(stainless steel)  <b>Casters:</b> 4+(2 leaving feet)  <b>Backup Battery:</b> Yes  <b>Temperature:</b> High/Low temperature, High ambient temperature  <b>Alarm:</b> Sensor error, system failure, door ajar, Main board communication error, USB data logger failure, condenser cooling failure, samples out of date  <b>Type:</b> Vertical  <b>External Size(W*D*H):</b> 790*1045*1950mm  <b>Weight:</b> 250kg  <b>Power Supply:</b> 220±10/50(V/HZ).  <b>Includes:</b> 5000 WATTS stabilizer  <b>Categories:</b> Air Conditioner, Regular  <b>Tags:</b> electronics, fridge stabilizer, fridge, home appliances, refrigerator, stabilizer, universal stabilizer  <b>Input Voltage:</b> 150 Volts  <b>Relay:</b> 3-4  <b>LOAD / CAPACITY:</b> 7500 WATTS  <b>Used For:</b> -86°C refrigerator  <b>PHASE:</b> Single</p>	01	
02	<p>Laboratory Trolley            Useful for general use.  <b>Shelf size:</b> 800x400 mm, total height 870 mm  <b>Weight approx:</b> 18 kg</p>	01	

03	<p>Day light LED/projector  <b>Native Resolution:</b> 800 x 600  <b>Maximum Resolution:</b> 1920 x 1200  <b>Standard Mode Brightness:</b> 3600 lm  <b>Native Aspect Ratio:</b> 4:3  <b>Compatible Aspect Ratio:</b> 16:9  <b>Contrast Ratio:</b> 20,000:1  <b>Throw Ratio:</b> 1.94 to 2.16 (51"@78.74")  <b>Digital Zoom:</b> 2x  <b>Vertical Keystone Correction:</b>  -40°/+40°  <b>Maximum Vertical Sync:</b> 120 Hz  <b>Maximum Horizontal Sync:</b> 100 kHz  <b>Minimum Vertical Sync:</b> 24 Hz  <b>Minimum Horizontal Sync:</b> 15 kHz  <b>Color Supported:</b> 1.07 Billion Colors (30-bit)  <b>Lens Type:</b> Manual Focus, Manual Zoom  <b>Minimum Lens Aperture:</b> F/21.85  <b>Maximum Lens Aperture:</b> F/24.01  <b>Minimum Focal Length:</b> 21.85 mm  <b>Maximum Focal Length:</b> 24.01 mm  <b>Minimum Diagonal Image Size:</b> 23"  <b>Maximum Diagonal Image Size:</b> 25 ft  <b>Minimum Projection Distance:</b> 39.37"  <b>Maximum Projection Distance:</b> 38.71 ft  <b>Optical Zoom:</b> 1.1x  <b>Lamp Type:</b> OSRAM  <b>Number of Lamps:</b> 1  <b>Lamp Power:</b> 203 W  <b>Normal Mode Lamp Life:</b> 4000 Hour  <b>Economy Mode Lamp Life:</b> 6000 Hour  <b>ExtremeEco Mode Lamp Life:</b> 10000 Hour  <b>HDMI:</b> Yes  <b>Number of USB Ports:</b> 1  <b>USB:</b> Yes  <b>USB Connector Type:</b> 1x Type-A  <b>Number of Composite Video Ports:</b>  1  <b>Composite Video:</b> Yes  <b>Number of VGA Inputs:</b> 1  <b>VGA In:</b> Yes  <b>Number Of Audio Inputs:</b> 1  <b>Audio Line In:</b> Yes  <b>Total Number of HDMI Ports:</b> 1  <b>Projection System:</b> DLP  <b>Projection Method:</b> Ceiling, Front, Rear, Rear Ceiling  <b>Video Compatibility:</b> EDTV, HDTV  NTSC, PAL, SDTV, SECAM  <b>Computer Compatibility:</b> Mac PC, Windows PC  <b>Number of Speakers:</b> 1  <b>Speaker Output Power:</b> 3 W  <b>Speaker Output Mode:</b> Mono  <b>Power Supply:</b> 100 V AC-240 V AC  <b>Input Voltage:</b>120 V AC; 230 V AC  <b>Operating Power Consumption:</b> 240 W  <b>Operating Power Consumption (Eco Mode):</b> 195 W  <b>Weight (Approximate):</b> 5.95 lb  <b>Includes:</b> AC Power Cord; Battery for Remote Control; Lens Cap; Quick Start Guide; Remote Control;  Security Card; VGA Cable; Carrying Case; Lamp (MC.JPV11.001); Ceiling Mount (MC.JLC11.003).</p>	01	
----	--	----	--

**Note: All the bidders are required to mention the details of their product being offered by them in the Technical proposal on firm's letter head duly signed & stamped by owner of firm or its authorized representative and also clearly mention the name & relevant major specifications of their offered product while quoting the financial bid as well. On firms letter head duly signed & stamped Mere reproduction of our tender documents will not serve the purpose and the bid may be liable to be rejected by the procuring agency in such cases.**

### Terms & Conditions

1. All material supplied must be brand new strictly conforming to the given specifications .Old, reconditioned or refurbished equipment shall not be acceptable.
2. Only certified dealers/distributors of the following manufacturers are eligible: **A standard company from etc.**

3. Prices should be FOR. If the items supplied are not according to the required specification/make it will have to be replaced by the firms on their own cost.
4. Offer must be supported with comprehensive technical literature and specifications in original (English) for the materials/goods offered.
5. Validity of rate should be for 120 days from the date of opening of tenders.
6. The vendors will be responsible for any damages during Transit/Delivery. They will also be responsible for any accident and their consequent damages.
7. Each page of tender documents should be signed and stamped by the bidder and attached with technical bid.
8. Key Person Contact No.0300-6872306

**Signature:** \_\_\_\_\_  
**Name:** \_\_\_\_\_  
**Designation:** \_\_\_\_\_  
**Date:** \_\_\_\_\_

**Attachments:**

Earnest Money draft	(Yes/No)
Affidavit for non-black listing	(Yes/No)
Bid Validity	(Yes/No)
Signed terms & conditions	(Yes/No)

**Note:** Bid shall be signed by the bidder/authorized person for bidder.

# Technical Specification offered by the firm required letter head of the firm duly signed & stamped by Vender of Tender A

01	<p>Ultra Low Temperature Freezer (-86 °C)</p> <p><b>Capacity:</b> 410L</p> <p><b>Temperature Range:</b> -40°C ~ 86°C</p> <p><b>Ambient Temperature:</b> 16°C – 32°C</p> <p><b>Cooling Performance:</b> -86°C</p> <p><b>Climate Class:</b> N</p> <p><b>Controller:</b> Microprocessor</p> <p><b>Display:</b> Touch Screen</p> <p><b>Compressor:</b> 2pcs (if one is damaged the other one give backup)</p> <p><b>Cooling Method:</b> Direct Cooling</p> <p><b>Refrigerant:</b> Mixture Gas</p> <p><b>Data Logging / Interval/ Recording Time:</b> USB/Record every 1 minute / 365 days</p> <p><b>Access Port:</b> 2pc. Ø 25 mm</p> <p><b>Door Lock with Key:</b> Yes</p> <p><b>External Lock:</b> Yes</p> <p><b>External Material:</b> High quality steel plates with spraying</p> <p><b>Internal Material:</b> Galvanized steel sheet</p> <p><b>Shelves:</b> 3(stainless steel)</p> <p><b>Casters:</b> 4+(2 leaving feet)</p> <p><b>Backup Battery:</b> Yes</p> <p><b>Temperature:</b> High/Low temperature, High ambient temperature</p> <p><b>Alarm:</b> Sensor error, system failure, door ajar, Main board communication error, USB data logger failure, condenser cooling failure, samples out of date</p> <p><b>Type:</b> Vertical</p> <p><b>External Size(W*D*H):</b> 790*1045*1950mm</p> <p><b>Weight:</b> 250kg</p> <p><b>Power Supply:</b> 220±10/50(V/HZ).</p> <p><b>Includes: 5000 WATTS stabilizer</b></p> <p><b>Categories:</b> Air Conditioner, Regular</p> <p><b>Tags:</b> electronics, fridge stabilizer, fridge, home appliances, refrigerator, stabilizer, universal stabilizer</p> <p><b>Input Voltage:</b> 150 Volts</p> <p><b>Relay:</b> 3-4</p> <p><b>LOAD / CAPACITY:</b> 7500 WATTS</p> <p><b>Used For:</b> -86°C refrigerator</p> <p><b>PHASE:</b> Single</p>
02	<p>Laboratory Trolley</p> <p>Useful for general use.</p> <p><b>Shelf size:</b> 800x400 mm, total height 870 mm</p> <p><b>Weight approx:</b> 18 kg</p>

03	<p>Day light LED/projector</p> <p><b>Native Resolution:</b> 800 x 600</p> <p><b>Maximum Resolution:</b> 1920 x 1200</p> <p><b>Standard Mode Brightness:</b> 3600 lm</p> <p><b>Native Aspect Ratio:</b> 4:3</p> <p><b>Compatible Aspect Ratio:</b> 16:9</p> <p><b>Contrast Ratio:</b> 20,000:1</p> <p><b>Throw Ratio:</b> 1.94 to 2.16 (51"@78.74")</p> <p><b>Digital Zoom:</b> 2x</p> <p><b>Vertical Keystone Correction:</b> -40°/+40°</p> <p><b>Maximum Vertical Sync:</b> 120 Hz</p> <p><b>Maximum Horizontal Sync:</b> 100 kHz</p> <p><b>Minimum Vertical Sync:</b> 24 Hz</p> <p><b>Minimum Horizontal Sync:</b> 15 kHz</p> <p><b>Color Supported:</b> 1.07 Billion Colors (30-bit)</p> <p><b>Lens Type:</b> Manual Focus, Manual Zoom</p> <p><b>Minimum Lens Aperture:</b> F/21.85</p> <p><b>Maximum Lens Aperture:</b> F/24.01</p> <p><b>Minimum Focal Length:</b> 21.85 mm</p> <p><b>Maximum Focal Length:</b> 24.01 mm</p> <p><b>Minimum Diagonal Image Size:</b> 23"</p> <p><b>Maximum Diagonal Image Size:</b> 25 ft</p> <p><b>Minimum Projection Distance:</b> 39.37"</p> <p><b>Maximum Projection Distance:</b> 38.71 ft</p> <p><b>Optical Zoom:</b> 1.1x</p> <p><b>Lamp Type:</b> OSRAM</p> <p><b>Number of Lamps:</b> 1</p> <p><b>Lamp Power:</b> 203 W</p> <p><b>Normal Mode Lamp Life:</b> 4000 Hour</p> <p><b>Economy Mode Lamp Life:</b> 6000 Hour</p> <p><b>ExtremeEco Mode Lamp Life:</b> 10000 Hour</p> <p><b>HDMI:</b> Yes</p> <p><b>Number of USB Ports:</b> 1</p> <p><b>USB:</b> Yes</p> <p><b>USB Connector Type:</b> 1x Type-A</p> <p><b>Number of Composite Video Ports:</b> 1</p> <p><b>Composite Video:</b> Yes</p> <p><b>Number of VGA Inputs:</b> 1</p> <p><b>VGA In:</b> Yes</p> <p><b>Number Of Audio Inputs:</b> 1</p> <p><b>Audio Line In:</b> Yes</p> <p><b>Total Number of HDMI Ports:</b> 1</p> <p><b>Projection System:</b> DLP</p> <p><b>Projection Method:</b> Ceiling, Front, Rear, Rear Ceiling</p> <p><b>Video Compatibility:</b> EDTV, HDTV NTSC, PAL, SDTV, SECAM</p> <p><b>Computer Compatibility:</b> Mac PC, Windows PC</p> <p><b>Number of Speakers:</b> 1</p> <p><b>Speaker Output Power:</b> 3 W</p> <p><b>Speaker Output Mode:</b> Mono</p> <p><b>Power Supply:</b> 100 V AC~240 V AC</p> <p><b>Input Voltage:</b> 120 V AC; 230 V AC</p> <p><b>Operating Power Consumption:</b> 240 W</p> <p><b>Operating Power Consumption (Eco Mode):</b> 195 W</p> <p><b>Weight (Approximate):</b> 5.95 lb</p> <p><b>Includes:</b> AC Power Cord; Battery for Remote Control; Lens Cap; Quick Start Guide; Remote Control; Security Card; VGA Cable; Carrying Case; Lamp (MC.JPV11.001); Ceiling Mount (MC.JLC11.003).</p>
----	---

