### The Islamia University of Wahawalpur

4

Annual/Special Repair for Cat-A House No. A-4 at Baghdad-ul-Jadeed Campus

MRS, Jul to Dec. 2024

|     |             | Annual/Special Repair for Cat-A House No. A-4 at Bagno   | 16              |           |       | I to Dec. 2024 |
|-----|-------------|--|-----------------|-----------|-------|----------------|
| No. | MRS Ref     | Description  | Quantity        | Unit Rate | Unit  | Amount         |
| 1   |             | Annual Repair Scraping Ordinary distemper, oil bound distemper, or paint of wall.  | 1,050.00<br>Sft |           | % Sft |                |
| 2   | 13/31-i+ii  | Preparing surface and painting with emulsion paint:- old surface 2 coats   | 7,578.00<br>Sft |           | % Sft |                |
| 3   | 13/4-c-i+ii | Painting Doors & Windows any type on old surface 2 Coats.  | 2,353.00<br>Sft |           | % Sft |                |
| 4   | 13/32A-b    | Providing and Applying of weather sheild paint of approved quality on external surface of building i/c preparation of surface application of primer complete in all respect old surface  | 8250.53<br>Sft  |           | % Sft | ÷              |
|     |             |  |                 |           | Total |                |
| 2   | 6/5-f       | Civil Work  Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1: 2: 4   | 57.00<br>Cft    |           | % Cft |                |
| 3   | 4/48        | Removing cement or lime plaster.   | 50.00<br>Sft    |           | %,Sft |                |
| 4   | 11/9-b      | Cement plaster 1:4 upto 20' (6.00 m) height:- ½" (13 mm) thick   | 450.00<br>Sft   |           | % Sft |                |
| 5   | 6/6         | (a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:- (3) (c) Type C (nominal mix 1: 2: 4)   | 15.50<br>Cft    |           | P/Cft | F              |
| 6   | 6/12-b      | Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars) deformed bar   | 33.50<br>Kg     |           | % Kg  |                |
| 7   | 12/13-b-ii  | First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze,12x12 meshes per square inches (5x5 per cm2) including iron fittings etc. complete:- Deodar wood framing 1½" (40 mm) thick, with wire gauze fixed in position:- ii) with springs or spring hinges  | 22.75<br>Sft    |           | P/Sft |                |
| 8   | 12/51       | Providing and fixing 1½" (40mm) thick solid flush door shutter sterling or equivalent with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.  | 22.75<br>Sft    |           | P/Sft |                |
| 10  | 7/5-i       | Pacca brick work in ground floor:- Cement, sand mortar:- Ratio 1:3   | 150.00<br>Cft   |           | % Cft |                |
| 11  | 25/40       | Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.  | 120.00<br>Sft   | e e       | P/Sft |                |
| 14  |             | Providing and laying superb quality Porcelain glazed tiles flooring of Master/ Stile brand or approved equivalent manufacturer of specified size in approved design, Color and Shade with adhesive/bond over 3/4"thick (1:3) cement plaster i/c the cost of sealer for finishing the joints i/c cutting grinding complete in all respect as approved and directed by the Engineer Incharge. (ii) 600mmx 600 mm  Providing and laying Prepolished Granite of specified thickness and shade of full width of approved quality laid with adhesive bond over 3/4" thick (1:2) cement | 125.00<br>Sft   |           | P/Sft |                |
|     |             | sand mortor bed , complete in all respect as approved and directed by the<br>Engineer Incharge. (ii) 1/2" thick  | 14.00<br>Sft    |           | P/Sft |                |

30-10-24

|     | MRS Ref  | Description  |                  |           |            |        |
|-----|----------|--|------------------|-----------|------------|--------|
| 1   | 12/61    | Providing and fixing almirab about   | Quantity         | Unit Rate | Unit       | Amount |
|     |          | Laminated/Glossy MDF (Karachi) sheet with 1"x3/4"deodar wood golla all around the leaf fixed on (3"x1") Kail wood frame i/c the cost of 1/2" full brass hinges, & frame i/c the cost of locking arrangement complete in all respect as approved  | 25.75            |           | P/Sft      |        |
| 18  | 12/62    | Providing and fixing 24" Deep Box type Wardrobe consisting of 3/4" thick UV coated MDF board(Medium density Fiber board) Sheet both side glazed shutters and box comprising of 3/4" thick laminated MDF sheet i/c the cost of 1mm thick PVC tape duly hot pressed on all edges of theshutters/ panels/ drawersetc., with machinei/c,thecost of self closing blum type hinges, handles, screws, Glue and rawal plugs, Drawers & locking arrangement complete in all respect as approved and directed by |                  |           |            |        |
|     |          | Engineer Incharge  | 84.00<br>Sft     |           |            |        |
|     |          |  |                  |           | Total      |        |
| 1   | 19/7-ii  | Plumbing Work  |                  |           |            |        |
|     | 1977-11  | Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc coloured, with pedestal   | 2.00             |           | Each       |        |
| 2   | 12/13-ii | Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   | No               |           |            |        |
|     |          | esimplicia. Galacia  | 2.00             |           | Each       |        |
| 3   | 19/4-ii  | Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   | No<br>1.00       |           | Each       | 9      |
| 4   | 19/35-ii | Providing and fitting "P" trap:- 10 cm (4") glazed.  | No<br>6.00       |           | Each       |        |
| 5   | 19/28    | Providing and fixing chromium plated tee stop cock '15mm (½").   | No<br>3.00       |           | Each       |        |
| 6   | 19/30    | Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.   | No<br>2.00       |           | Each       |        |
| 7   | 19/27-ii | Providing and fixing chromium plated bib cock:- 1.5 cm (½")  | No<br>2.00<br>No |           | Each       |        |
| 8   | 19/23    | Providing and fixing Bathroom Accessories (7-piece set) Master brand One Cosmetic Shelf, One Towel rod with bracket, One soap dish, One double hook, One towel ring, brush holder, toilet paper holder & looking glass i/c the cost of hardwares etc complete in all respect as approved and directed by the Engineer incharge.  | NO               |           |            |        |
| i   |          | plastic soap dish  | 2.00<br>No       |           | Each       |        |
| ii  |          | plastic toilet paper holder  | 2.00<br>No       |           | Each       |        |
| iii |          | plastic towel rail   | 2.00<br>No       | 9         | Each       |        |
| iv  |          | plastic shelf 60x13 cm (24"x5") with bracket and railing.  | 2.00<br>No       |           | Each       |        |
| 9   |          | Looking glass with plastic frame  Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC   | 2.00<br>No       |           | Each       |        |
| $ $ |          | pipe line with `B' Class working pressure pipe, in trenches, complete in all respects:- 4" i/d (100 mm)  | 39.00            |           | •<br>P/Rft | *      |
|     |          | 6" i/d (150 mm)  | Rft<br>65.00     |           | P/Rft      |        |
|     |          |  | Rft              |           |            |        |

P- 2/3

30-8-29

|     | t                  |  |                     |           |       |          |
|-----|--------------------|--|---------------------|-----------|-------|----------|
| 1   | MRS Ref            |  |                     |           |       |          |
| 0   | 19/52-ii           | Providing and fixing CP bath Room Set made of Sonex/Master/Faisal comprising of 3-No Tee stop cocks, lever type Paris At 1   | Quantity            | Unit Rate | Unit  | Amount   |
| M   |                    | comprising of 3-No Tee stop cocks, lever type Basin Mixer, double Bib  |                     |           |       | Alliount |
|     |                    | Cock, open wall shower Market Stop Cocks, lever type Basin Mixer, double Bib   |                     |           |       |          |
|     |                    | Cock, open wall shower, Muslim shower, waste coupling and bottle trap etc. complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect as approved and direct to the complete in all respect to the complete in all resp |                     |           |       |          |
|     |                    | etc. complete in all respect as approved and directed by the Engineerincharge.   |                     |           |       |          |
|     | i                  | Lever Type Basin Mixer   |                     |           |       |          |
|     |                    | Level Type Basin Mixer   | 2.00                |           | Each  |          |
|     | ii                 | 3 No Too Stee O  | No                  |           | Lacii |          |
|     |                    | 3 No Tee Stop Cock (set)   | 2.00                |           | Eách  |          |
|     | iti                | David Division   | No                  |           | Lacii |          |
|     | 101                | Double Bib Cock  | 2.00                |           | Each  |          |
|     | 1                  |  | No                  |           | Lacii |          |
|     | iv                 | Muslim shower  | 3.00                |           | Each  |          |
|     |                    |  | No.                 |           | Lacii |          |
|     | V                  | Waste Coupling   | 3.00                |           | Each  |          |
|     | AND THE RESERVE OF |  | No.                 |           | Lacii |          |
| 11  | 19/1-i             | Providing and fitting glazed earthen ware water closet European type.  | 140                 |           |       |          |
|     |                    | excluding seat and cover:-   | 2.00                |           | Each  |          |
|     |                    | NA COST AND RESIDENCE AND A COST  | No.                 |           | Lacii |          |
| 12  | 19/2-i             | Providing and fixing doubt   | 1.00                |           |       |          |
|     |                    | Providing and fixing, double seat and cover only bakelite  | 1000-000            |           | Each  |          |
| 13  | 19/8               | Providing and fiving attaints and the state of the state  | No                  |           |       |          |
| "   | 10/0               | Providing and fixing stainless steel sink with drain board, size 120x60 cm   | 4.00                |           | _ ,   |          |
|     |                    | (48"x24") including bracket set, waste pipe and waste coupling.  | 1.00                |           | Each  |          |
| 14  | 23/46a             | Providing levies to the  | No                  |           |       |          |
| ' ' | 201400             | Providing, laying, testing and commissioning of POLYPROPYLENE  |                     |           |       |          |
|     |                    | RANDOM COPOLYMER (PPRC) water supply pipe (Dadex /Popular/   |                     |           | - 1   |          |
|     |                    | Beta or equivalent) with specified pressure rating PN (PRESSURE  |                     |           | .     |          |
|     |                    | NOMINAL) and conforming to DIN 8077-8078 code i/c cost of solvent,   |                     |           |       |          |
|     |                    | specials,making jharries complete in all respect as approved and   |                     |           |       |          |
|     |                    | directed by Engineer Incharge.(Internal/External Diameters mentioned).   |                     |           | - 1   |          |
|     | 54                 | PN-20 pipe   | 138 140120110011401 |           |       |          |
|     |                    | (ii)(3/4") 25 mm   | 110.00              |           | P/Rft |          |
|     | 21                 | (55) (AII) 20 mm   | Rft                 |           |       |          |
|     |                    | (iii)(1") 32 mm  | 90.00               |           | P/Rft |          |
| -   |                    |  | Rft                 |           |       |          |
|     |                    |  |                     |           | Total |          |

P- 3/3

Executive Engineer (M)

30-8-28

# The Islamia University of Wahawalpur

## Annual Special Repair for Cat-A House No. A-2 at Baghdad-ul-Jadeed Campus

MRS, Jul to Dec. 2024

| MRS Ref   Description   Quantity   Unit Rate   Unit   Amount   Annual Repair   Screping Ordinary distemper, oil bound distemper, or part of vall.   2,755.62   % Sft   Stt   13/31-H+  Preparing surface and painting with emulsion paint - old surface 2 coats   10,780.44   % Sft   Sft   31/34-C-H+  Painting Doors & Windows any type on old surface 2 Coats   2,780.00   % Sft   Sft   13/33   Providing and Applying of weather shelid paint of approved quality on external surface of building its preparation of surface application of primer complete in all respect old surface   Sft   70 ct          |     | MRS, Jul to Dec. 2024 |  |  |           |   |        |  |
|--|-----|-----------------------|--|--|-----------|---|--------|--|
| Annual Repair Scraping Ordinary distemper, oil bound distemper, or paint of wail.  2 13/31-thi Preparing surface and painting with enulsion paint - old surface 2 cools 3 13/4-ci-thi Preparing surface and painting with enulsion paint - old surface 2 cools Sft 2 789.00 Sft 2 789.00 Sft 3 13/33 Providing and Applying of weather shelfd paint of approved quality on external surface of building i/c preparation of surface application of primer complete in all respect old surface  1 4/19-c Civil Work Comment concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate); (f) Ratio 12:4 Comment concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate); (f) Ratio 11:2-4 Comment plaster 1-4 upto 20' (6.00 m) height. '%' (13 mm) thick Sft T50.00 Sft T50.00 Sft Providing and laying superit quality Ceramic tile footor of Master brand of specified size, Glossy/Matrif value of approved cofor and Shade as per approved appeal with archives be instite is culting griding complete in all respects and a spacewish and diverse bents of culting griding complete in all respects and a spacewish and diverse bents is culting griding complete in all respects and a spacewish and diverse bents is culting griding complete in all respects and a spacewish and bents bents in the culting griding complete in all respects and a spacewish archives bents in the culting griding complete in all respects and a spacewish and superious and diverse bents in a culting griding complete in all respects and a spacewish and superious and diverse bents in a culting griding complete in all respects and a spacewish and bent and spacewish      | No. | MRS Ref               | Description  | Quantity   | Unit Rate | Unit                                    | Amount |  |
| Scraping Ordinary distemper, all bound distemper, or praint of wall  2 13/31-Hst Preparing surface and painting with emulsion paint - old surface 2 coats Stt 10,786.44  3 13/4-c-Hst Painting Doors & Windows any type on old surface 2 Coats Stt 2,780.00 Stt 2,780.00 Stt 2,780.00 Stt 3/5-1  4 13/33 Providing and Applying of weather shelid paint of approved quality on external surface of building tip preparation of surface application of primer complete in all respect old surface  Civil Work Dismantling cement concrete 12.4 plain  Cement concrete plain including placing_compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1 1/9-b Cement concrete plain including placing_compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1 1/9-b Cement plaister 1.4 upto 20' (6.00 m) height - ½' (1.3 mm) thick Stt 750.00 Stt 750     |     |                       |  |  |           |   |        |  |
| 49-b of paint of wall  Preparing surface and painting with emulsion paint - old surface 2 cools  \$\frac{1}{3}\] 13/41-\text{-141} Preparing surface and painting with emulsion paint - old surface 2 cools  \$\frac{1}{3}\] 13/4-ci-til  Painting Doors & Windows any type on old surface 2 Cools  \$\frac{1}{3}\] 13/33  Providing and Applying of weather shelid paint of approved quality on external surface of building its preparation of surface application of prime rompiete in all respect old surface  1 4/19-c Civil Work  Civil Work  Cement concrete plain including placing_compacting_finishing and curing complete (including screening and washing of stone aggregate); (f) Ratio 12.2.4  3 4/48 Removing cement or lime plaster.  1 1/9-b Cement plaster 1-4 upto 20' (6.00 m) height - ½'' (13 mm) thick  5 10/24-i  1 10/24-i  5 2 4/48 Removing cement or lime plaster.  Cement plaster 1-4 upto 20' (6.00 m) height - ½'' (13 mm) thick  \$\frac{1}{5}\] 10/24-i  1 10/24-i  5 10/25-i  6 10/25-i  Providing and laying superis quality Ceramic tile floors of Master brand of specified size, Glosyflatt (Fourier of approved Color and Shade as per approved dosign with architective bond, over 34" thick (1.2) ceramic tiles dad of Master brand of specified size, Glosyflatt (Fourier of approved Color and Shade as per approved dosign with architective bond, over 34" thick (1.2) ceramic tiles dad of Master brand of specified size, Glossyflatt (Fourier of approved Color and Shade as per approved and increded by the Engineer incharge 12"x18"/12"x24"/10"x24"/2"x32"/10"x24"  Froviding and laying superis quality Ceramic tiles dad of Master brand of specified size, Glossyflatt (Fourier of approved Color and Shade specified size, Glossyflatt (Fourier of approved Color and Shade specified size, Glossyflatt (Fourier of approved Color and Shade specified size, Glossyflatt (Fourier of approved Color and Shade specified size, Glossyflatt (Fourier of approved Color and Shade specified size, Glossyflatt (Fourier of approved Color and Shade specified size, Glossyflat | 1   |                       |  |  | 1         |   |        |  |
| 2 13/31-i+iii Prepaning surface and painting with emulsion paint - old surface 2 coots 3 13/4-c-i+iii Painting Doors & Windows any type on old surface 2 Coots 4 13/33 Providing and Applying of weather shelld paint of approved quality on external surface of building if or preparation of surface application of primer complete in all respect old surface  1 4/19-c Dismantling cement concrete 1/2.4 plain.  2 6/6-f Cement concrete plain including placing.compacting, finishing and curing complete (including screening and washing of stone aggregate). (f) Ralio 1, 2.4  3 4/48 Exmoving cement or lime plaster.  Cement plaster 1 4 upto 20' (6.00 m) height - ½" (13 mm) thick 5 10/24-i  1 10/24-i  1 10/24-i  1 10/24-i  1 10/24-i  1 10/24-i  1 10/25-i       |     | 4/49-h                | or paint of wall   | 2 755 62   |           | % Sft                                   |        |  |
| 13/31-i+u    Preparing surface and painting with emulsion paint - old surface 2 coals   10,786.44   % Sft   31/4-ci-i+u    Painting Doors & Windows any type on old surface 2 Coals   2,760.00   % Sft   13/33   Providing and Applying of weather shelid paint of approved quality on external surface of building lic preparation of surface application of primer complete in all respect old surface   14/19-c   14/19-c   15/51       | 1   | 17 10 0               | or paint of wall.  | Committee of the Commit |           |   |        |  |
| 3 13/4-c-i+ii Painting Doors & Windows any type on old surface 2 Coats 4 13/33 Providing and Applying of weather shelid paint of approved quality on external surface of building lic preparation of surface application of str.   1 4/19-c Civil Work 1 4/19-c Dismantling cement concrete 1.2 4 plain. 2 6/5-1 Cement concrete plain including placing,compacting, finishing and curing complete (including screening and washing of stone aggregate); (f) Ratio 1.2 4 3 4/48 Removing cement or lime plaster. 4 11/9-b Cement plaster 1.4 upto 20° (6.00 m) height:- ½° (13 mm) thick 750.00 Stt.  5 10/24-i Providing and laying superb quality Ceramic tile floors of Master brand of specified size, ClossyMautTexture of approved Color and Shades appropried and directed by the Engineer Incharge 12*x16*712*x24*710*x24*   1 10/25-i Providing and laying superb quality Ceramic tiles dade of Master brand of specified size, ClossyMautTexture of approved Color and Shades approved and directed by the Engineer Incharge 12*x16*712*x24*710*x24*   1 19/7-ii Providing and laying superb quality Ceramic tiles dade of Master brand of specified size, ClossyMautTexture of approved Color and Shade washed to over 12*tick 112*x24*710*x24**   1 19/7-ii Providing and laying superb quality Ceramic tiles dade of Master brand of specified size, ClossyMautTexture scirtic/glade of approved Color and Shade washed to over 12*tick 112*x24*710*x24**   1 19/7-ii Providing and laying superb quality Ceramic tiles dade of Master brand of specified size, ClossyMautTexture scirtic/glade of approved Color and Shade washed to over 12*tick 112*x24*710*x24**   1 19/7-ii Providing and fitting glazed earthen ware wash hand basin i/antly 56*x40 cm (22*x16*) including bracks etc. (poper connection, etc. conquete Color and Shade washed based based by the Engineer incharge 12*x16*712*x24*710*x26** (2 000 Each No Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracks etc. copper connection, etc. conquete Color and Providing and f     |     | 10/04 :               |  |  |           | 0/ 00                                   |        |  |
| 3 13/4-c-i+ii Painting Doors & Windows any type on old surface 2 Coats.  4 13/33 Providing and Applying of weather shelid paint of approved quality on external surface of building lic preparation of surface application of primer complete in all respect old surface.  5 1 4/19-c Civil Work Dismantling cement concrete 1:2.4 plain.  Cement concrete plain including placing.compacting, finishing and curing complete (including screening and washing of stone aggregate); (f) Ratio 1:2:4  3 4/48 Removing cement or lime plaster.  4 11/9-b Cement plaster 1 4 upto 20' (6.00 m) height:- ½" (13 mm) thick St St St St 10/24-i Providing and laying superit quality Ceramic life floors of Master brand of specific size of linesynflator feature of approved Color and Shade as per approved of sealer for finishing the joints \(\frac{1}{2}\) cutter floors of Master brand of specific size, Glossynflator feature shade size, Providing and laying superit quality Ceramic life stone of Master brand of specific size, Glossynflator feature of approved Color and Shade as per approved and directed by the Engineer Incharge 12*x18*712*x24*710*x24*  6 10/25-i Providing and laying superb quality Ceramic lifes dade of Master brand of specific size, Glossynflator feature shirting/dade of approved Color and Shade what addises benotic over 12*tick (12) cement patter for the cost of sealer for finishing the joints \(\frac{1}{2}\) cutter finite finite diagrading complete in all respects and as approved and directed by the Engineer Incharge 12*x18*712*x24*710*x24* 18*x24*712*x39*  6 10/25-i Providing and litting glazed earther ware wash hand basin avanity \$\$x40 cm 2.2.00 Knth addises benotic over 12*tick (12) cement patter for the cost of sealer for finishing bracket set, exper connection, set complete Colorured No No Providing and fitting plastic made low down flushing cistern 13.65 litre (3 gallons) capacity, including bracket set, exper connection, set complete Colorured No No Providing and fitting plastic made low down flushing cistern 13.65 litre (3 gal   | 2   | 13/31-1+11            | Preparing surface and painting with emulsion paint - old surface 2 coats   | 10,786.44  |           | % SIL                                   |        |  |
| # Painting Doors & Windows any type on old surface 2 Coats   |     |                       |  | Sft  |           |   |        |  |
| # Painting Doors & Windows any type on old surface 2 Coats   | 3   | 13/4-c-i+ii           |  | 2 700 00   |           | % Sft                                   |        |  |
| Providing and Applying of weather shelld paint of approved quality on external surface of building its preparation of surface application of primer complete in all respect old surface    1   | "   | 10/10/11              | Painting Doors & Windows any type on old surface 2 Coats.  | 200 C C C C C C C C C C C C C C C C C C  |           | 100000000                               |        |  |
| external surface of building life preparation of surface application of primer complete in all respect old surface  1 4/19-c Civil Work Dismantling cement concrete 1:2.4 plain.  2 6/5-f Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1:2.4  3 4/48 Removing cement or lime plaster.  4 11/9-b Cement plaster 1.4 upto 20' (6.00 m) height - ½" (13 mm) thick St. St. T50.00 %      |     |                       |  | Sit  |           |   |        |  |
| external surface of building if to preparation of surface application of primer complete in all respect old surface    1   4/19-c   Civil Work   Dismantling cement concrete 1:2.4 plain   72.97 Cft   % Cft   Cft   Cment concrete plain including placing.compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1:2.4   Removing cement or lime plaster.   % Cft   750.00 Cft   750.00 Sft       | 4   | 13/33                 | Providing and Applying of weather shelld paint of approved quality on  |  |           |   |        |  |
| primer complete in all respect old surface    1  | 1   | -                     | external surface of building i/c preparation of surface application of   |  |           | % Sft                                   |        |  |
| Civil Work Dismantling cement concrete 1:2.4 plain.  Cement concrete plain including placing,compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1:2.4  Removing cement or lime plaster.  Removing cement or lime plaster.  This is a straight of the plaster of the plaste     |     |                       |  | 12.1   |           | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, |        |  |
| 1  |     | 2                     |  | SIL  |           | Total                                   |        |  |
| 1 4/19-c Dismantling cement concrete 1:2.4 plain. 2 6/5-f Cement concrete plain including placing.compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1:2:4 3 4/48 Removing cement or lime plaster. 3 1/19-b Cement plaster 1:4 upto 20' (6.00 m) height- ½' (13 mm) thick 5th 750 00 5th 750 0     |     |                       |  |  |           |   |        |  |
| 1 4/19-c Dismantling cement concrete 1:2.4 plain. 2 6/5-f Cement concrete plain including placing.compacting, finishing and curing complete (including screening and washing of stone aggregate): (f) Ratio 1:2:4 3 4/48 Removing cement or lime plaster. 3 1/19-b Cement plaster 1:4 upto 20' (6.00 m) height- ½' (13 mm) thick 5th 750 00 5th 750 0     |     |                       | Civil Work   |  |           | % Cft                                   |        |  |
| 2 6/5-f Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate). (f) Ratio 1. 2: 4  3 4/48 Removing cement or lime plaster.  4 11/9-b Cement plaster 1:4 upto 20' (6.00 m) height: - ½" (13 mm) thick 750 00 Sft 750 00 S     | 1   | 4/19-c                |  |  |           | 70 011                                  |        |  |
| complete (including screening and washing of stone aggregate). (77 Notes 1.2.4   1.2.4   Removing cement or lime plaster.   750.00   |     | 1X 77.30 845A         |  | Cft  |           |   |        |  |
| complete (including screening and washing of stone aggregate). (77 Notes 1.2.4   1.2.4   Removing cement or lime plaster.   750.00   | 2   | 6/5-f                 | Cement concrete plain including placing, compacting, finishing and curing  |  |           |   |        |  |
| 1 2: 4  Removing cement or lime plaster.  Cft 750.00 Stt 750.00 St     | 1   | 0,01                  | complete (including screening and washing of stone aggregate): (f) Ratio   | 450  |           | % Cft                                   |        |  |
| 4 4/48 Removing cement or lime plaster.  4 11/9-b Cement plaster 1.4 upto 20' (6.00 m) height: - ½" (13 mm) thick  5 10/24-i  5 10/24-i  6 10/24-i  7 10/24-i  7 10/24-i  8 10/24-i  1 10/25-i  2 1 10/25-i  3 1 10/25-i  2 1 10/25-i  2 1 10/25-i  3 1 10/25-i  2 1 10/25-i  3 1 10/25-i  4 1 1 10/25-i  5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1   |     |                       | 1. 2. 4  | F (2004 CO)  |           | ,, ,,,                                  |        |  |
| 4/48 Removing cement or lime plaster  11/9-b Cement plaster 1.4 upto 20' (6.00 m) height: - ½" (13 mm) thick  5 10/24-i  10/24-i  10/24-i  Providing and laying superb quality Ceramic title floors of Master brand of specified size. Glossy/Matt/Texture of approved Color and Shade as per approved design with adhesive bond, over 3/4" hick (1/2) cement sand plaster is the cost of sealer for finishing the joints is custing grinding complete in all respects and as approved and directed by the Engineer Incharge 12"x18"/12"x24"/10"x24"  10/25-i  Providing and laying superb quality Ceramic titles dado of Master brand of specified size. Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 12"x18"/12"x24"/10"x24"/8"x24"/12"x36"  10/25-i  Providing and laying superb quality Ceramic titles dado of Master brand of specified size. Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 12"x18"/12"x24"/10"x24"/8"x24"/12"x36"  150 00 F/Sft  11/9/7-ii  19/7-ii  10 m (4") glazed.  10 m (4") glazed.  10 m (5")  10 m (6 m (   |     |                       | 1. 2. 4  |  |           | % Sft                                   |        |  |
| 4 11/9-b Cement plaster 1:4 upto 20' (6.00 m) height: - ½" (13 mm) thick 750.00 Sft 750.     | 3   | 4/48                  | Removing cement or lime plaster.   |  |           | /0 OIL                                  |        |  |
| 11/9-b Cement plaster 1:4 upto 20' (6.00 m) height: -½' (1.3 min) thick  5 10/24-i  10/24-i  10/24-i  10/24-i  10/24-i  10/24-i  10/25-i       | ١٠  | 4/40                  | 1  | 500,000,000  |           | 0/ Cft                                  |        |  |
| 5 10/24-i Providing and laying superb quality Ceramic tile floors of Master brand of specified size, Glossy/Matt/Texture of approved Color and Shade as per approved design with adhesive bond, over 3/4" thick (1/2) cement sand plaster ive the cost of sealer for finishing the joints ic cutting grinding complete in all respects and as approved and directed by the Engineer Incharge 12"x18"/12"x24"/10"x24" 42.00 Sft 10/25-i Providing and laying superb quality Ceramic tiles dado of Master brand of specified size, Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 1/2"thick (1-2) cement plaster i/c the cost of sealer for finishing the joints i/c cutting grinding complete is all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24"/12"x36" Sft 150.00 Sft 75tt 150     | ١,  | 11/0 h                | Cement plaster 1:4 unto 20' (6.00 m) height:- ½" (13 mm) thick   |  |           | % SIL                                   |        |  |
| Providing and laying supers quality Ceramic tiles and Shade as per approved specified size glossy/Mattrexture of approved Color and Shade as per approved design with adhesive bond, over 34" thick (1,2) cement sand plaster inc the cost of sealer for finishing the light of mishing the light of grading complete in all respects and as approved and directed by the Engineer Incharge 12"x18"/12"x24"/10"x24"  8   | 4   | 11/9-0                | Cement plaster 1st apre 25 (5555)  | Sft  |           |   |        |  |
| Providing and laying supers quality Ceramic tiles and Shade as per approved specified size glossy/Mattrexture of approved Color and Shade as per approved design with adhesive bond, over 34" thick (1,2) cement sand plaster inc the cost of sealer for finishing the light of mishing the light of grading complete in all respects and as approved and directed by the Engineer Incharge 12"x18"/12"x24"/10"x24"  8   | ے ا | 10/24 i               |  | 1  |           |   |        |  |
| specified size, GlossyMattTexture of approved color and Shade as place specified size, GlossyMattTexture of approved specified size, GlossyMattTexture of sealer for finishing the joints i/c cutting grinding complete in all respects and as approved and directed by the Engineer Incharge 12"x18"/12"x24"/10"x24"  10/25-1  Providing and laying superb quality Ceramic tiles dado of Master brand of specified size, GlossyMattTexture skirting/dado of approved Color and Shade with adhesive bond over 172thick (1:2) coment plaster i/c the cost of sealer for finishing the joints i/c cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24"/8"x24"/12"x36"  119/7-ii  Plumbing Work  1 19/7-ii  Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16" including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal  2 12/13-ii  Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  No  19/4-ii  Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  No  19/35-ii  Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  No  19/38-ii  Providing and fitting in plastic made low flushing cistern flushing fitting in the providing and fitting chromium plated tee stop cock '15mm (½").  No  19/27-ii  Providing and fixing chromium plated bib cock: 1.5 cm (½")  No  Each  No  150     | 2   | 10/24-1               | Providing and laying superb quality Ceramic tile floors of Master brand of   |  |           |   |        |  |
| design with adhesive bond, over 34'-tinok (1)-gentlent sain counting grinding complete in all respects and as approved and directed by the Engineer Incharge 12'x18''12'x24''10'x24'' 42.00 Stt    10/25-1  Providing and laying superb quality Ceramic tiles dado of Master brand of specified size, Clossy/Matt/Texture skirling/dado of approved Color and Shade with adhesive bond over 1/2'thick (1.2) cement plaster to the cost of sealer for finishing the joints id cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12'x18''12'x24''10'x24''12''x36'' 150 00 Stt    Plumbing Work.  Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (2'2'x16'') including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal    2 12/13-ii  Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   No  19/4-ii  Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   No  19/35-ii  Providing and fitting "P" trap:- 10 cm (4") glazed.   6.00 Each   No  Providing and fixing chromium plated be stop cock '15mm (½").   No  Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.   7 19/27-ii  Providing and fixing chromium plated bib cock:- 1.5 cm (½")   No  Providing and fixing chromium plated bib cock:- 1.5 cm (½")   |     | 1                     | I a Manuffacture of approved Color and office as per approved  |  |           | - 1                                     |        |  |
| approved and directed by the Engineer Incharge 12 X16 / 12 X24 / 12 X36 / Stt  |     |                       | The state bond over 3/4" thick it is certified add plaster to the  | 250  |           |   |        |  |
| 10/25-1   Providing and laying superb quality Ceramic tiles dado of Master brand of specified size Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 1/2 thick (1.2) cement plaster i/c the cost of sealer for finishing the joints i/c cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24"/8"x24"/12"x36"   150 00 Sft   |     |                       | of sealer for finishing the joints i/c cutting grinding complete in all tests and by the Engineer Incharge 12"x18"/12"x24"/10"x24" |  |           | D.10()                                  |        |  |
| Providing and laying superb quality Ceramic tiles dado of Master brand of specified size, Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 1/2*thck (1.2) cement plaster i/c the cost of sealer for finishing the joints vic cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12*x18*/12*x24*/10*x24*/8*x24*/12*x36**   19/7-ii   Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22*x16*) including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal   Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   No.   No.   Each   No.   Each   No.   No.   No.   No.   No.   Each   No.   No.   Each   No.   No.   Each   No.   No.   Each   No.       |     |                       |  | 240000000000000000000000000000000000000  |           | P/Stt                                   |        |  |
| Providing and laying superb quality Ceramic tiles dado of Master brand of specified size, Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 1/2"thick (1:2) cement plaster \( \text{if the cost of sealer for finishing the joints \( \text{if c cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and of titing glazed earthen ware wash hand basin \( \text{vanity incharge in all respects as approved and of titing glazed earthen ware wash hand basin \( \text{in incharge in all respects as approved and of titing glazed earthen ware water closured. 2.00  Each  \text{No}  \text{No}   \text{No}   \text{No}   \text{No}  |     |                       | /8 X24 / 12 X30  | Sft  |           |   |        |  |
| Providing and laying superb quality Ceramic tiles dado of Master brand of specified size, Glossy/Matt/Texture skirting/dado of approved Color and Shade with adhesive bond over 1/2"thick (1:2) cement plaster \( \text{if the cost of sealer for finishing the joints \( \text{if c cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" \( \text{if if incharge in all respects as approved and of titing glazed earthen ware wash hand basin \( \text{vanity incharge in all respects as approved and of titing glazed earthen ware wash hand basin \( \text{in incharge in all respects as approved and of titing glazed earthen ware water closured. 2.00  Each  \text{No}  \text{No}   \text{No}   \text{No}   \text{No}  | ١,  | 10/05                 |  |  |           | '                                       |        |  |
| specified size, Glossy/Matt/Texture skirting/dado of approved cition and shaw with adhesive bond over 1/2"thick (1-2) cement plaster for the cost of sealer for finishing the joints of cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12"x18"712"x24"/10"x24"/8"x24"/12"x36"  1 19/7-ii  Plumbing Work  1 19/7-ii  Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured. with pedestal  2 12/13-ii  Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  No  1 19/4-ii  Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  1 19/35-ii  Providing and fitting "P" trap:- 10 cm (4") glazed.  Providing and fixing chromium plated tee stop cock "15mm (½").  No  1 19/30  Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower  7 19/27-ii  Providing and fixing chromium plated bib cock:- 1.5 cm (½")  No  Providing and fixing chromium plated bib cock:- 1.5 cm (½")  No  Providing and fixing chromium plated bib cock:- 1.5 cm (½")   | 16  | 10/25-1               | - A Louise superb quality Ceremic tiles dado of Master brand of  |  |           |   | i      |  |
| with adhesive bond over 1/2'thick (1:2) cement plaster in the costs as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" /8"x24"/12"x36"  1 19/7-ii   Plumbing Work   Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal   Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   No   No   Each   No   No   Each   No   Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   2.00   Each   No        |     |                       | Providing and laying superb quality Geranno these data of which are given and Shade  |  |           |   |        |  |
| finishing the joints i/c cutting grinding complete in all respects as approved and directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" /8"x24"/12"x36"  1 1977-ii  Plumbing Work Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal  Providing and fitting plastic made low down flushing cistern 13 63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  No  19/4-ii Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  No  19/35-ii Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28 Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½") No  Each No  Froviding and fixing chromium plated bib cock:- 1.5 cm (½")   |     |                       | with adhesive hand over 1/2"thick (1:2) cement plaster i/c the cost of sealer for  |  |           | l                                       |        |  |
| directed by the Engineer Incharge. 12"x18"/12"x24"/10 x24" / 8 x x 4 / 12 x 36  Sft  Total    19/7-ii   Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal    2   12/13-ii   Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   2   12/4-ii   Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   3   19/4-ii   Providing and fitting "P" trap:- 10 cm (4") glazed.   4   19/35-ii   Providing and fixing chromium plated tee stop cock "15mm (½").   5   19/28   Providing and fixing chromium plated tee stop cock "15mm (½").   6   19/30   Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.   7   19/27-ii   Providing and fixing chromium plated bib cock:- 1.5 cm (½")   1.00   Each No  |     |                       | Spicking the joints i/c cutting grinding complete in all respects as approved and  | 150.00   |           | D/Sft                                   |        |  |
| 1   19/7-ii   Plumbing Work   Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured with pedestal   2.00 No   Each No   No   Each No   No   No   No   No   No   No   No   |     |                       | directed by the Engineer Incharge. 12"x18"/12"x24"/10"x24" /8"x24"/12"x36"   |  |           | 7510                                    |        |  |
| 1   19/7-ii   Plumbing Work   Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22°x16°) including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal   2.00 No   Each No   No   Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   2.00 No   Each No   No   Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   2.00 No   Each No   No   Providing and fitting "P" trap:- 10 cm (4") glazed.   6.00 Each No   No   No   Each No   No   Each No   No   Each No   No   No   Each No   No   No   Each No   No   No   Each No   No   Each No   No   No   Each No   No   No   Each No   No   No   No   No   Each No   No   No   No   No   No   No   No   |     |                       |  | Sit  |           |   |        |  |
| 1   19/7-ii   Plumbing Work   Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22°x16°) including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal   2.00 No   Each No   No   Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured   2.00 No   Each No   No   Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   2.00 No   Each No   No   Providing and fitting "P" trap:- 10 cm (4") glazed.   6.00 Each No   No   No   Each No   No   Each No   No   Each No   No   No   Each No   No   No   Each No   No   No   Each No   No   Each No   No   No   Each No   No   No   Each No   No   No   No   No   Each No   No   No   No   No   No   No   No   |     |                       |  |  |           | Total                                   |        |  |
| 1 19/7-ii Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal  2 12/13-ii Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  3 19/4-ii Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  4 19/35-ii Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28 Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  1 1.00 Each  |     |                       |  |  |           |   |        |  |
| (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal   2.00 No   |     |                       | Plumbing Work  |  |           |   |        |  |
| (22"x16") including bracket set, waste pipe and waste coupling, etc. coloured, with pedestal   2.00 No   |     | 1 19/7-ii             | Providing and fitting glazed earthen ware wash hand basin /vanity 56x40 cm   |  |           |   |        |  |
| 2 12/13-ii Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  No  19/4-ii Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  4 19/35-ii Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28 Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½") 1.00 Each No     |     |                       |  | 2.00   |           | Each                                    | 1      |  |
| 2 12/13-ii Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  3 19/4-ii Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  4 19/35-ii Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28 Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  1 1.00 Each  |     |                       | with pedestal  |  |           |   | 1      |  |
| Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete. Coloured  19/4-ii  19/4-ii  Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  2.00  No  Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28  Providing and fixing chromium plated tee stop cock '15mm (½").  6.00  No  Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii  Providing and fixing chromium plated bib cock:- 1.5 cm (½")  1.00  Each  No  The providing and fixing chromium plated bib cock:- 1.5 cm (½")  Each  No  Each   |     |                       |  | NO   |           |   | 1      |  |
| capacity, including bracket set, copper connection, etc. complete. Coloured  19/4-ii  19/4-ii  Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured  2.00 No No Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28  Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30  Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii  Providing and fixing chromium plated bib cock:- 1.5 cm (½")  1.00 No Each No Dividing and fixing chromium plated bib cock:- 1.5 cm (½")  1.00 No Each No Dividing and fixing chromium plated bib cock:- 1.5 cm (½")  1.00 No Each No Dividing and fixing chromium plated bib cock:- 1.5 cm (½")  1.00 No Each   | 2   | 2   12/13-ii          | Describes and fitting plantic made law down flushing dieters 13.63 litre (3 gallons)   |  |           |   | 1      |  |
| 19/4-ii   Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   2.00 No   |     |                       | Providing and fitting plastic made low down liusting distern 15.05 little (5 gallons)  | 2.00   |           | Each                                    |        |  |
| 19/4-ii   Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest. Coloured   2.00 No No  |     |                       | capacity, including bracket set, copper commenter, etc. complete.  |  |           |   |        |  |
| (Orisa pattern), combined with foot rest. Coloured  4 19/35-ii Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28 Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Each No  Each      | ١,  | 40/4 ::               | Providing and fitting glazed earthen ware water closet, squatter type  | .,.  |           |   |        |  |
| Providing and fitting "P" trap:- 10 cm (4") glazed.  No 6.00 No 6.00 Providing and fixing chromium plated tee stop cock '15mm (½").  Providing and fixing chromium plated mixing valve, for wash hand basin, sink or shower  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Ro 6.00 No Each No 19/30 Each No 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Each No 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")   | 13  | 19/4-11               | (Orisa pattern), combined with foot rest. Coloured   | 2.00   |           | Each                                    |        |  |
| Providing and fitting "P" trap:- 10 cm (4") glazed.  5 19/28 Providing and fixing chromium plated tee stop cock '15mm (½").  6 19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  8 6.00 No  8 6.00 No  8 2ach No  19/30 Each No  19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  |     |                       | V  | No   |           | -2                                      |        |  |
| Providing and fixing chromium plated tee stop cock '15mm (½").  Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Each No  Ro  Bach No  Each No  |     | 10/25 #               | Providing and fitting "P" tran: 10 cm (4") glazed  |  |           | Fach                                    | 1      |  |
| Providing and fixing chromium plated tee stop cock '15mm (½").  19/30 Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Each No No No Each No  | 1 " | 19/33-11              | Providing and numy F trap 10 on (4 ) grazed.   |  |           | Lucii                                   |        |  |
| Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  No  Rach No  No  Each No No   |     | 10:00                 |  |  |           | [                                       |        |  |
| Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  Each No No No  | 5   | 19/28                 | Providing and fixing chromium plated tee stop cock '15mm (½").   |  |           | Each                                    |        |  |
| sink or shower.  7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½")  8 3.00 No No Each No No   |     |                       |  | No   |           |   |        |  |
| 7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½") No 1.00 Each No   | 6   | 19/30                 |  |  |           |   |        |  |
| 7 19/27-ii Providing and fixing chromium plated bib cock:- 1.5 cm (½") 1.00 Each   |     |                       | sink or shower.  |  |           | Each                                    |        |  |
| No No  | _   | 40/07                 | Desiration and fining absention plated his section 4.5 (4/11)  |  |           |   |        |  |
|  | 7   | 19/27-11              | Providing and fixing chromium plated bib cock:- 1.5 cm (½")  |  |           | Each                                    |        |  |
| $\mathcal{D} \mathcal{M}$  |     |                       | P- 1/2   | INO  |           |   |        |  |

| o. MRS I |            | Description   | Quantity           | Unit Rate | Unit         | Amount |
|----------|------------|---|--------------------|-----------|--------------|--------|
| 19/2     | C          | Providing and fixing Bathroom Accessories (7-piece set) Master brand -One cosmetic Shelf, One Towel rod with bracket, One soap dish, One double hook, one towel ring, brush holder, toilet paper holder & looking glass i/c the cost of ardwares etc complete in all respect as approved and directed by the Engineer nicharge.   |                    |           |              |        |
|          |            | plastic soap dish   | 2.00<br>No         |           | Each         |        |
| i l      | p          | plastic toilet paper holder   | 2.00               |           | Each         |        |
| i        | þ          | plastic towel rail  | No<br>2.00         |           | Each         |        |
| v        |            | plastic shelf 60x13 cm (24"x5") with bracket and railing.   | No<br>2.00         |           | Each         |        |
| ,        |            | Looking glass with plastic frame  | No<br>2.00         |           | Each         |        |
| 9 23/2   | 6-b        | Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line  | No<br>·            |           |              |        |
|          | ,          | with 'B' Class working pressure pipe, in trenches, complete in all respects:- 4" i/d (100 mm)   | 39.00<br>Rft       |           | P/Rft        |        |
| 23/2     | 27-d       | 6" i/d (150 mm)   | 52.00<br>Rft       |           | P/Rft        |        |
| 10 19/5  |            | Providing and fixing CP bath Room Set made of Sonex/Master/Faisal comprising of 3-No Tee stop cocks, lever type Basin Mixer, double Bib Cock, open wall shower, Muslim shower, waste coupling and bottle trap etc. complete in all respect as approved and directed by the Engineerincharge.  |                    |           |              |        |
|          | i          | Lever Type Basin Mixer  | 1.00<br>No         |           | Each         |        |
|          | ii         | 3 No Tee Stop Cock (set)  | 1.00<br><b>N</b> o |           | Each         |        |
|          | iii        | Double Bib Cock   | 1.00<br>No         |           | Each         |        |
|          | iv         | Muslim shower   | 1.00<br>No<br>1.00 |           | Each<br>Each |        |
| 11 10    | v<br>9/1-i | Waste Coupling  Providing and fitting glazed earthen ware water closet European type,   | No<br>1.00         | ľ         | Lacii        |        |
| 11   19  | 57 1-1     | excluding seat and cover:-  | No                 | E         | Each         |        |
| 12 19    | 9/2-i      | Providing and fixing, double seat and cover only bakelite   | 1.00<br>No         | E         | Each         |        |
| 13 1     | 9/8        | Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.  | 2.00<br>No         | E         | Each         |        |
| 14 23    | 3/46a      | Providing, laying, testing and commissioning of POLYPROPYLENE RANDOM COPOLYMER (PPRC) water supply pipe (Dadex /Popular/Beta or equivalent) with specified pressure rating PN (PRESSURE NOMINAL) and conforming to DIN 8077-8078 code i/c cost of solvent, specials, making jharries complete in all respect as approved and directed by Engineer Indoorse (Internal) Properties monthly and provided in the properties of the properties |                    |           |              |        |
|          |            | directed by Engineer Incharge.(Internal/External Diameters mentioned). (ii)(3/4") 25 mm   | 140.00<br>Rft      | F         | P/Rft        |        |
|          |            | (iii)(1") 32 mm   | 75.00<br>Rft       | F         | P/Rft        |        |
|          |            |   |                    | 7         | otal         |        |

Executive Engineer (M)

30-8-24

#### The Islamia University of Bahawalpur

University Online: www.iub.edu.pk

#### TENDER NOTICE (SINGLE STAGE, FINANCIAL PROPOSAL ONLY)

No 801/XEN-Engg.

Dated: 30/August/2024

- 1 Sealed tenders on the basis of Market Rates System invited from the approved contractors of the IUB, who have got their names enlisted / renewed in the appropriate category for the financial year 2023-24, besides having valid registration in the relevant category with Pakistan Engineering Counsel.
- 2 The tender form will be received as per time schedule mentioned in the tender notice by the M&R works tender opening committee in the office of the Executive Engineer (M), The Islamia University of Bahawalpur. The tenders will be opened in presence of the contractors or their authorized agents who care to remain present on the occasion on the same day.
- 3 The contractor who desire to obtain tender form shall have to submit an application on his printed letter pad in addition, tenders of contractors will only be considered who will produce bid security in shape of original Call Deposit Receipt in favour of Executive Engineer (M), The Islamia University of Bahawalpur from firms owned account and along with the following original documents and their attested copies
  - Enlistment / Renewal fee for the financial year 2023 2024 with the IUB.
  - b) Registration certificate issued by the Pakistan Engineering Council for the year 2023-24.
  - c) C.N.I.C
  - d) Receipt of professional tax.
  - e) Company / firm registration certificate.
  - f) Managing partnership deed of the firm along with registered power of attorney.
  - g) Authorized letter with the agent if he appears on behalf of company / firm.
- 4 The blank tender forms / bidding documents can be purchased immediately after the publication date from the office of the Executive Engineer (M), The Islamia University of Bahawalpur at nonrefundable cost mentioned against work, up to the office hours as per time schedule mentioned in the tender notice. The same are also available on the PPRA / IUB website and these may be downloaded free of cost. No tender form / bidding document will be sold on the date of receipt of tenders.
- 5 The tenders must be delivered in person or through authorized agent nominated by company to the tender opening committee in sealed envelope. Any tender if received by post or through any other means shall not be accepted.
- 6 The conditional, incomplete and overwritten tenders shall be rejected.
- 7 Earnest Money of the estimated cost of work in shape of Deposit at call drawn in favour of the Executive Engineer (M), The Islamia University of Bahawalpur from a scheduled bank must accompany with the tender
- 8 The procuring agency may reject all bids or proposals at any time prior to the acceptance of bid or proposal
- 9 The procuring agency shall upon request communicate to any bidder, the ground for its rejection of all bids or proposals but shall not be required to justify those grounds
- 10 The work will be executed according to the approved drawings by the competent authority. All the detail can be seen from the office of the undersigned during office hours
- 11 In case of any dispute, the case will be referred to the Treasurer, The Islamia University of Bahawalpur whose decision shall be final and binding on both the parties
- 12 The payment will be made as per actual work done subject to availability of fund and clearance by the M&R works committee and Inspection Committee or any other agency nominated by the IUB from time to time
- 13 Letter of Acceptance / approval of tender will be subject to availability of funds.
- 14 During execution of the work if any damage to the work occurs, the contractor will be responsible for it and no claim shall be acceptable.
- 15 No interest shall be paid to the Contractor on account of any delay in making payment by the department for the work done.
- 16 Successful / Lowest evaluated bidder will be required to furnish the performance guarantee / quality assurance security (wherever required) from scheduled bank before entering into a contract. The lowest evaluated bidder refuse or fail for any reason to furnish the performance guarantee / quality assurance security, it should constitute a just cause for rejection of his tender / annulment of award and in event of such rejection / annulment, the entire earnest money shall be forfeited to IUB, as compensation for such default.
- 17 According to contract document clause 26(A) and Finance Department Notification vide

  No.RO(TECH) FD 1-2/2017 dated 16th November 2022, in case the total tendered amount is equal to or less than 5% of the
  approved estimate (DNIT) amount of contractual works / civil works mentioned above notification, the lowest bidder will have to
  deposit quality assurance security from the Scheduled Bank equal to the amount of difference between approve DNIT amount and
  the quoted bid amount of contractual works / civil works, within 15 days of issuance of notice or within expiry period of bid,
  whichever is earlier.

- At the time, the Executive Engineer (M) informs the lowest bidder in writing, bidder will provide performance guarantee / quality assurance security (wherever required) within 15 days from the receipt of letter, failing which his bid will be rejected and bid security will be forfeited.
- 19 Tender will only be sold to owners of firm or their authorize representatives having authority letter on judicial e-stamp paper duly issued in owner's name in dates after issuing this notice. No tender will be sold to any other person.
- 20 Any error / omission / discrepancy in the description and unit of BOQ items, the corresponding MRS item will be prevailed and considered.



Executive Engineer (M)
The Islamia University of
Bahawalpur
Baghdad ul Jadeed Campu

Phone: 062-9255459